

MODEL	SAUNA SIZE (m³)	OUT-PUT (kW)	WID x DEP x HEI (mm)	SAFETY DISTANCE FROM STOVE (mm)			WATER TANK (l)	FLUE OPENING Ø (mm)	DISTANCE FROM CENTRE OF UPPER FLUE OPENING TO BACK EDGE (mm)	REAR FLUE OPENING HEIGHT OF FROM FLOOR (mm)	WEIGHT WITHOUT STONES (kg)	STONE CAPACITY (kg)
				FRONT	SIDES (water tank side)	BACK						
WOOD BURNING STOVES WITH WATER TANKS												
KARHU-12V	5–10	12	575x480x660	500	500	500	25	104	140	450	53	40
KARHU-20V	8–17	18	650x480x780	500	500	500	28	104	140	513	67	60
KARHU-27V	17–27	20	650x480x920	500	500	500	28	129	140	640	77	65
KARHU-37V	25–34	30	730x580x920	500	500	500	28	129	140	640	125	75
KS-12V	5–9	12	590x510x660	500	500 (150)	500	25	104	110	450	53	40
KS-12VV	5–9	12	590x510x660	500	500 (150)	500	25	104	110	450	53	40
KL-16VE	8–15	15	435x675x710	500	500	500	22	104	110	505	60	40
KS-20V	8–17	18	655x510x780	500	500 (150)	500	28	104	140	513	67	60
KS-20VV	8–17	18	655x510x780	500	500 (150)	500	28	104	140	513	67	60
KS-20VVV	8–14	18	820x510x780	500	(150)	500	2 x 28	104	140	513	71	60
KS-27V	15–24	20	655x510x920	500	500 (150)	500	28	129	140	640	77	65
KS-27VV	15–24	20	655x510x920	500	500 (150)	500	28	129	140	640	77	65
KS-27VVV	15–21	20	820x510x920	500	(150)	500	2 x 28	129	140	640	81	65
KS-37V	23–34	30	740x610x920	500	500 (150)	500	28	129	145	640	125	75
KS-37VV	23–34	30	740x610x920	500	500 (150)	500	28	129	145	640	125	75
KS-37VVV	23–31	30	900x610x920	500	(150)	500	2 x 28	129	145	640	130	75
KSIS-20V	8–16	18	655x490x786*	500	500 (150)	500	28	129	140	Connection only from top	80	60
KSIS-20VV	8–16	18	655x490x786*	500	500 (150)	500	28	129	140	Connection only from top	80	60
KSIS-27V	17–26	20	655x490x920*	500	500 (150)	500	28	129	140	Connection only from top	90	65
KSIS-27VV	17–26	20	655x490x920*	500	500 (150)	500	28	129	140	Connection only from top	90	65
KO-20+VK-20	8–17	18	670x546x928	500	200 (150)	200	28	129	165	532	99+10	60
KT-S-20+VK-20	8–17	18	670x546x928*	500	200 (150)	500	28	129	165	Connection only from top	119+10	60
KT-H-20+VK-20	8–17	18	670x546x928*	500	200 (150)	500	28	129	165	Connection only from top	119+10	60

KS-12, KS-20, KS-27 ja KS-37 stoves height adjustable in front legs. V = Water tank to the right of door. VV = Water tank to the left of door. VVV = Water tank on both sides. *) measurements from sauna side.

Choose a correctly sized wood burning stove from our large range

Visible tile or glass surfaces raise effective volume of sauna. Add 3 cubic metres for each square metre of tile or single plate glass wall that exceeds 2 square metres. If the sauna's walls are uninsulated log, add 25% to volume. In edge cases always choose the larger stove.

Choose correctly sized stones

For wood burning stoves the stones must have a minimum diameter of 10 cm.

Every Kastor wood burning stove comes with a three year warranty for the material.